Nobili Mulcher Product Guide

QUALITY • INNOVATION • RELIABILITY



a Louis A shid



B



silvan.com.au

Nobili Mulcher Range

CHOOSING THE RIGHT MULCHER

Floating top link allows machine

to follow ground contours

Nobili has developed their design and manufacturing techniques since the company first made agricultural equipment in 1945. Today the company operates under the strict quality guidelines of ISO 9001 certification. Nobili mulchers are designed to get the best performance in all agricultural applications and to suit various tractor HP categories.

The theory behind mulchers is simple; they cut grass, prunings and heavier organic material repeatedly, instead of just once. Mulchers are fitted with at least one cutting bar along with special blades that act in unison to cut the material finer. The material circulates inside the mulcher as the blades cut it again and again. A finer residue is then evenly distributed, which decomposes quickly into humus, improving

URATOR

soil quality. This allows non productive land to be quickly returned to pasture in a single pass.

Mulching returns the nutrients in prunings and grass to the soil. Mulch contains nitrogen, phosphorus and potassium; a complete set of nutrients. The decomposing mulched material increases nitrogen levels and reduces fertiliser requirements.

Mulchers can be applied to a wide range of applications including; general clearing, weed management, pasture topping, orchard and vineyard use, parks and gardens management, roadside maintenance and crop residue management.

> Components are fully painted before assembly increasing corrosion protection

Over run clutch in gear box for driveline protection

Chassis made from high resistance steel

> Precision balanced rotors for vibration-free operation

Quality belts for high power transmission

mulch large prunings, while high body mulchers are best suited to high volumes of material (e.g. crop stubble) and allow a higher

Most machines are fitted with wear skids to protect the mulcher

body but working skids are recommended on machines without

Rear roller or wheels are designed to maintain a consistent

working height. Wheels often allow a higher ground speed to be

maintained while a rear roller is best suited to uneven ground

ground speed to be maintained.

wheels or roller

5. HEIGHT CONTROL: SKIDS, WHEELS OR ROLLER

Supporting skids

1. WHAT IS THE APPLICATION?

- Orchard, vineyard, pasture, etc. (refer to Nobili Mulcher Range). 2. WHAT IS THE TRACTOR HORSE POWER?
- Nobili has mulchers suited to tractors from 40HP to over 450HP. Working widths from 95 to 820cm are available.
- 3. WILL PRUNINGS BE MULCHED? Refer to Nobili Mulcher Range for the model suited to the prunings size.
- 4. IS THE MATERIAL VERY BULKY?
- Low body mulchers are suited to low volumes of material but can



Knife and hammer blade options to suit the application



Double skin or wear plate options for increased working life



Hydraulic and manual side-shift options



because it covers the full machine width. Many Nobili mulcher

the ground speed is not compromised.

material could pass through the machine.

6. WHAT OPTIONS ARE REQUIRED?

models allow the mulched material to pass over the roller so that

Replaceable wear plates should be considered if heavy or foreign

Hydraulic side shift is suited to applications where there are

varying row widths or mulching under tree canopies is necessary.

Roller and wheel options for accurate height control

1300 745 826 silvan.com.au

Nobili Mulcher Range

THE RIGHT TOOL FOR THE JOB

ge	ß	B	B	
GRASS				

		TYPE OF LINKAGE			PRUNINGS/WOOD		GRASS					INTER-	DEGO		
MODEL		FRONT	REAR	APPLICATION	VINE Shoots < 5cm	CUT Wood < 8CM	CUT WOOD < 10CM	INTER ROW VINES/ ORCHARDS	UNDER- GROWTH	PASTURE	PARKS And Gardens	FALLOW LAND FALLOW CROPS & CROP RESIDUE	CROPS & CROP	RECO TRACTOR POWER (HP)	WORKING WIDTHS (CM)
ORCHARD/VINEYARD	νк		1	Orchard or vineyard mulcher with manual offset and full width roller	1			1						35 - 70	95 /115/135/155
	VKD		1	Versatile mulcher with full width roller and optional hydraulic sideshift		1		1	1	1		1		50 - 100	155/170/190/210/230
	BV PRO		1	Heavy duty orchard mulcher with full width roller and optional hydraulic sideshift			1	1	1	1		1		75 - 130	170/190/210
	TRP	+	1	Mulcher suited to stony ground with pick up front			1							60 - 150	95/120/145/175
	BNE		1	Economical mulcher suited to vineyards	1			1		1	1			40 - 95	120/150/180/210
	TLP		1	Grass mulcher suited to low HP tractors						1	1			20 - 30	120/135/160
GRASS/PASTURE	BKE	+	1	Grass and pasture topping mulcher with optional reversible gearbox and hydraulic sideshift	1			1	1	1	1			40 - 150	210/230/250
GRASS	BP10	+	1	Versatile mulcher with optional reversible gearbox and hydraulic sideshift	\$			1		1	1			40 - 150	240/280/300
	BNG		1	High body mulcher suited to pasture topping and general clearing		1		1	1	1		1	1	70 - 125	230/270
CROP RESIDUE MULTI-PURPOSE	VKM		1	Suited to general clearing or orchard use with hydraulic side shift and double skin		1		1	1	1		1	1	70 - 150	210/240/280/305
	RMII		1	General clearing or vineyard use			1	1	1	1			1	50 - 130	150/180/210
	BNU		1	General clearing or vineyard use		1		1	1	1			1	40 - 125	120/160/190
	BK		1	Heavy duty mulcher for pasture topping, general clearing or stubble management		1		1	1	1		1	1	70 - 175	230/280/320
	BPR	1	1	General clearing or orchard use with full width roller	1				1	1	1	1	1	70 - 175	240/280/305
	RM		1	Heavy duty mulcher for stubble management		1				1		1	1	90 - 280	240/280/320/400/450
	NK7/ RM8		1	Suited to crop residue management eg. pineapples, bananas			1	1	1			1	1	100 - 190	210/240
	RMS		1	Heavy duty mulcher for stubble management with dual drive		1				1		1	1	180 - 450	560/610/820
OFFSET/ROADSIDE	TB		1	Offset mulcher for on-farm use						1	1			60 - 110	150/180/210
OFF SET/R	TBE		1	Heavy duty offset mulcher for council and contractor use	\$				1	1	\$	\$	\$	80 - 170	190/220/240









de de de a



Nobili Mulcher Range - CHOOSING THE RIGHT MULCHER

jo jo . Jo . Jo



BV PRO



Nobili Mulcher Range

CHOOSING THE RIGHT MULCHER



SILVAN AUSTRALIA PTY. LTD. ABN 48 099 851 144

QLD. Office: Warehouse 2, 30 Gow St, Moorooka, QLD 4105

W.A. Office: 12 Cressall Road, Balcatta, WA 6021

New Zealand: 22 Sunshine Avenue, Hamilton, 3241

Fax: 1800 745 826

Web: silvan.com.au

Web: silvannz.co.nz Fax: 07 849 6070

Freecall: 1300 745 826

Email: info@silvanaust.com

Email: infonz@silvanaust.com

Head Office: 244-264 Greens Road.

Dandenong South, Vic, Australia 3175

All items in this catalogue have been included in good faith on the basis that the goods described were available at the time this catalogue was published. Failure of suppliers to deliver in accordance with samples, descriptions, or at all, or other unintentional causes may result in some lines being unavailable. Space may prevent some participating dealers from stocking all items. All brand names and product names used in this publication are trade names, registered trade marks, or pending trade marks of their respective owners.

© SILVAN AUSTRALIA PTY. LTD. 2017

LIA PTY. LTD. 2017 Phone: 0508 745 826 Fa For more information call 1300 745 826 or visit www.silvan.com.au



NSBIL ®