

PRODUCT FACT SHEET

Silvan Australia Pty. Ltd.
244 – 264 Greens Rd
Dandenong South VIC 3175



PRODUCT NAME (DESCRIPTION)	600L SKID SPRAY WITH 12V REEL TUFF REMOTE REEL
Part Number	L06H4-42R147
Barcode (EAN)	9337027048717



PRODUCT FEATURES	BENEFITS
1. 600L Tank with drainage sump.	1. Drain sump for easy cleaning.
2. Comet APS41 pump for 40 Bar max pressure backed by HondaGX160 5.5HP.	2. Hi pressure pump that suits a wide array of farm or commercial spray applications.
3. Galvanised Steel Skid.	3. Resistant scuffs, scratches and corrosion for a long-lasting quality.
4. REEL TUFF 12V Remote Hose Reel.	4. Galvanised Heavy duty, high torque direct drive reel.
5. Fitted with 100m of ½" O.D. hose and Turbo 400 Spray gun.	5. Ideal for roadside spraying, through undulating scrub, poultry sheds or glasshouses.

Specifications	
Pump	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. APS41 38L/min capacity, 6000kPa, direct driven by 5.5HP Honda GX160 with 6:1 reduction gearbox. Controls: Pressure regulator with gauge and 1 spare outlets for another hose reel or accessory equipment.
Tank	600L, Polytuff impact resistant tank with non-spill screw down lid and drainage sump.
Frame	Fully Galvanised Steel sled frame.
Filtration	<ul style="list-style-type: none"> Coarse Basket screen filter at tank opening for coarse debris. Easy-to-access, easy-to-clean suction screen filter to keep fine material out of the pump and nozzle.
REEL TUFF Hose Reel	<ul style="list-style-type: none"> Heavy duty thick gauge steel construction for superior resistance corrosion and scratches. Electric direct drive system via patented gearbox drive assembly eliminated the use of chains, belts and sprockets for more reliable and safer working conditions. This means that there are no belts or chains that need to be regularly checked and tensioned. 12V DC High Torque electric motor direct coupled to gearbox, max 25amp draw (under maximum load) with 4 meters of power cable for user connection. Reel Hub Position lock with spring loaded Pin-lock with ratchet mechanism keeps hose safely on the reel and prevents hose or spraygun damage in transport. <p>Remote Control: Single channel control 915mhz with adaptive frequency hopping prevents interference for reliable performance across undulating terrain. Rubber sheathed for protection supplied fitted with 9V battery.</p> <p>Reel Mounted Controls: On / Off power switch and manual override rewind switch.</p>
Hose & Spray Gun	<ul style="list-style-type: none"> 100m of ½" O.D kink resistant nylon tubing, hard wearing and low friction. Hose stopper to prevent the complete length of hose being wound into the reel and keeps hand and spray gun away from the hose guide. Turbo 400 Spray gun and hose swivel with adjustable spray lever to control the spray pattern from a pencil stream for spraying distant objects to fine atomised spraying for increased surface coverage. Liquid Shut-off Snap coupling at spray gun to allow easy change or storage of spray gun
User Access	<ul style="list-style-type: none"> Designed for user safety with Left Hand Side (Non-Road Side) controls and adjustment Side mounted engine and pump regulator allow for the best access for starting and pump adjustments without stretching or reaching over a hot engine Side mounted tank allows for easy access to the tank opening for filling while standing next to a vehicle mounted skid
Dimensions: Height 750mm, Length 1200mm, Depth 1850mm, Weight 215kg (empty)	