

DESCRIPTION

PRODUCT NAME:	Fire Fighter Trailer 1100L Honda/Davey GX160, 30m Hose reel & Fast filler.
PART NUMBER:	SLF1000D-1-BLV
BARCODE:	9337027045426
CATEGORY:	9

PRODUCT

HEAVY DUTY GALVANISED TRAILER
LARGE CAPACITY TANK WITH INTERNAL BAFFLE
30M HOSE REEL ADJ FIRE FIGHTING NOZZLE.
DAM FILL KIT

BENEFITS

ROVER Vehicle compliant & certified.
 Allows operator to deliver water through the nozzle for up to 55 mins. Internal Baffle to reduce surge when travelling.
 Ideal for Firefighting, plant machinery wash down and watering of plants/Trees etc.
 Factory fitted dam fill kit, for fast filling the tank from a dam or other water storage, approx. 4 min fill time.

SPECIFICATIONS

Tank

- 1100L U.V stabilised polyethylene with large 455mm filling lid with breather and strainer basket.
- Internal **BAFFLE** to reduce surge when travelling.

Trailer

- Hot dipped galvanised finish
- Heavy duty leaf spring suspension
- 5 Stud Ford wheels and 235/15AT (All Terrain) Tyres
- Adjustable jockey wheel and 50mm tow hitch.
- ADR approved Mechanical overrun brakes
- LED Tail lights, indicators & registration plate light.
- VIN Plate attached for on road registration
- **ROVER Vehicle Compliant & Certified**
- **Note:** The Trailer is road registerable, which is the responsibility of the owner.

Honda Engine

- 4 stroke, 5.5 Hp GX160
- Manual recoil rope start
- Low oil protection, Oil used SAE 10W 30 (600ml)
- Twin stage foam prefilter with paper final element
- Fuel tank Capacity 3.6 Litres (Unleaded)
- Approx fuel consumption @ full load 1.7L per hour.

Davey Pump Specifications

Viton equipped

- internal seal, O-rings & gaskets.
- Fitted for improved chemical resistance.

Important:

- Please seek specialist advice from chemical supplier if pumping chemicals.
- Use of aggressive chemicals may void warranty.

Pump performance

- Maximum output 475 (L/min), Max Pressure 50 (PSI)
- Direct coupled single centrifugal impeller
- Inlet 1 x 1.5" Outlets 2 x 1.5" (Spare) 2 x 1".
- 2 x 1" used for the Hose reel & 3-way valve to deliver water back to the tank.



Hose reel

- Manual wind, Heavy duty powder coated steel.
- 30m ¾" ID delivery hose
- Adjustable nozzle, approximate flow rate 20L/min
- At full load, distance of water directed from the adjustable nozzle can be up to approximately 20mtrs.

Dam fill kit (Factory fitted)

- 6m suction hose and filter with camlocks for easy use and storage.
- 1 x 3-way valve fitted to the pump that changes the position of suction from the tank to suction hose in the Dam fill kit
- 1 x Ball valve fitted to deliver water from the pump to the tank.
- **Refill time on maximum load, approx. 4 minutes.**

Dimensions

- Length 3800mm x Width 1820mm x Height 1530mm, Weight (empty 440kg)

Warning! Do not exceed the vehicle manufacturer's specified safe load and carrying capacity.

Warranty – 12 months

Version 1.2

5.12.24