

12 VOLT 200 LITRE SELECTA BLUE TRANSFER UNIT

- Designed for the storage and transfer of AUS32 Solution
- UV Stabilized polytuff tank
- 35L/min open flow self priming pump
- 4m of 3/4" delivery hose with manual nozzle
- 3m long power cord with alligator clips



TKA200-7

CODE	DESCRIPTION	LENGTH	WIDTH	HEIGHT	WEIGHT	LIST EX	LIST INC	CAT
TKA200-7	12 Volt 200L Selecta Blue Transfer Unit	1030mm	580mm	530mm	21kg	\$926.36	\$1,019.00	Α

MANUAL LEVER PUMP

- Chemical resistant, appropriate for water, lubricants, mild detergents and agricultural chemicals
- Approx 0.5L per stroke
- Materials: Polypropylene, Polyethylene, Acetal
- Temperature Range: -5C to +45C
- 2" BSP Connection





PF56

CODE	DESCRIPTION	OPEN FLOW	LIST EX	LIST INC	CAT
PF56	Manual Lever Pump	Approx 0.5L per stroke	\$113.64	\$125.00	В

[†]AdBlue® is a registered trademark of the VDA *Optional extra hose is available, customer fitment.

K24 METER

- Display can rotate to four positions
- 1" BSP M/M with 1" socket for M/F or M/M installation
- Working flow rate 6-100L/min
- Accuracy to +/- 1%
- Adjustable calibration
- Resolution to 0.1L
- Batch total to 99999L
- Complete total to 999999L
- View flow rate L/min
- Suitable for urea, water, windscreen washing liquid, basic ag chemicals



CODE	DESCRIPTION	WEIGHT	LIST EX	LIST INC	CAT
F00407090	K24 Meter (1 socket)	0.4 kg	\$490.91	\$540.00	Α

