

# 4000L G2E TGS Vineyard Sprayer



Pictured: 3 Row 4000L G2E TGS

## MODEL SPECIFICATIONS

<b>HEAD</b>	Multi row spraying head with air assist diffusers and twin spray nozzles. Each air diffuser features swivel adjustment and air deflector. Poly air tubes shaped to surround canopy. Left and right arms have independent hydraulic fold with manual width and height adjustment. (2 sets of tractor remotes required).		<b>CHEMICAL INDUCTION</b>	Venturi suction probe.				
	<b>PUMP</b>	Silvan oil-backed diaphragm type with nitrile diaphragms with brass heads and manifolds. IDS2001: 182L/min. capacity 5000kPa pressure.		<b>FRAME</b>	Galvanised steel chassis, adjustable drawbar & heavy duty stand.			
<b>FAN SIZE</b>		500mm twin impeller turbine fan, power consumed 48 kw (64HP).		<b>AGITATION</b>	Pump bypass and twin venturi agitators.			
<b>NOZZLES</b>	Twin hollow cone ceramic nozzles per outlet with individual metering on/off non-drip taps.		<b>PRESSURE GAUGE</b>	Glycerine filled gauge located on the valve bank.				
<b>GEARBOX</b>	2-speed with neutral position, oil-bath type.		<b>FILTRATION</b>	Suction line filter and pressure filter.				
<b>CONTROLS</b>	40 Bar electric section valves, master valve, electric pressure regulator and in cab controls.		<b>WHEEL EQUIPMENT</b>	Tandem simplicity suspension with 11.5 x 15.3" tyres.				
<b>MAIN TANK</b>	Polytuff impact resistant polyethylene construction with calibrated sightline & 50mm camlock top & bottom fill.		<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi constant velocity (wide angle) driveshaft with quick release pins & safety cover.				
<b>HAND WASH TANK</b>	Polytuff tank filled through cap. Located next to bottom fill.		<b>HP REQUIRED</b>	Minimum 75 PTO HP.				
			<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG(DRY)</b>	
			<b>ETG44NF6S2</b>	5230	less head	1950	3300	1820
					folded	2800		
Length measured with drawbar in shortest position.								

MODEL DESCRIPTION	CODE
2 ROW 4000L G2E TGS: IDS2001 pump, electric valve controls, 500mm twin turbine fan	ETG44NF6S2
3 ROW 4000L G2E TGS: IDS2001 pump, electric valve controls, 500mm twin turbine fan	ETG44NM6S3
FACTORY OPTIONS	CODE
IDS2600 pump, 249L/min capacity, 5000kPa pressure	D99-149
Bravo 180S automatic rate controller	D99-143
Vertical lift head assembly (1 extra set of tractor remotes required)	TGS-LIFT
Quick turning hitch	D99-170
Twin galvanised snorkel	D99-172
Hydraulic row width adjustment	-
Road kit	D99-151
Over row work lights	D99-152