

Cane Boom - Linkage Sprayer



Pictured: 1100L with 6 row cane boom

MODEL SPECIFICATIONS				
PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP60/20: 58 L/min. capacity 2000kPa pressure. BP75/20: 71 L/min. capacity 2000kPa pressure. BP125/20: 121 L/min. capacity 2000kPa pressure.			
BOOM	Cane boom: 4 row or 6 row. Fully galvanised construction, to suit row widths from 1.5 - 1.8m with 500-1300mm shield spray head and brush skirts. Spray heads have heavy duty hinges to withstand drag, parallelogram tracking system.			
NOZZLES	2 x twin nozzle bodies per spray head and air induction nozzles.			
CONTROLS	4 outlet single lever control valve with pressure regulation and gauge.			
TANK	Low profile 600/800/1100L Polytuff impact resistant polyethylene construction, external sightline with floating ball and non-spill offset screw-down lid with single breather. 15L freshwater tank with screw-down lid and on/off tap. 4L toolbox with polythylene lid. 50mm Camlock bottom fill and venturi chemical suction probe (1100L only).			
FRAME	Fully galvanised steel, cat II adjustable hitch.			
AGITATION	Bypass agitation.			
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.			
FILTRATION	Lid strainer and suction line strainer with stop valve fitted at side of tank to enable ease of filter maintenance.			
PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
K06N-60C	1025	1150	1300	105
K08N-75C	1350	1395	1315	145
K11NH-75C	1350	1395	1610	160

MODEL DESCRIPTION	CODE
600L LINKAGE SPRAYER BP60/20 pump, no boom	K06N-60C
600L LINKAGE SPRAYER BP125/20 pump, no boom	K06N-125C
800L LINKAGE SPRAYER BP75/20 pump, no boom	K08N-75C
800L LINKAGE SPRAYER BP125/20 pump, no boom	K08N-125C
1100L LINKAGE SPRAYER BP75/20 pump, no boom	K11NH-75C
1100L LINKAGE SPRAYER BP125/20 pump, no boom	K11NH-125C
BOOM OPTIONS	CODE
4 ROW CANE BOOM	035-4N
6 ROW CANE BOOM	035-6N
Broadacre boom attachment (to suit 4 row)	035-4B
Broadacre boom attachment (to suit 6 row)	035-6B
Hydraulic lift, galvanised single hydraulic system	032-40DL
FACTORY OPTIONS	CODE
70L flush tank kit to flush the filter, spraylines and nozzles	K99-47
Electric control 3 section with in cab pressure adjustment	K99-29
Electric control 4 section with in cab pressure adjustment	K99-49
Electric control 5 section with in cab pressure adjustment	K99-50
Bravo 180S automatic rate controller	J99-151
Silmix chemical hopper	K99-21

Note: Not all options will fit all models.
Extra charges may apply to fitment of some options.