Trailed Turf Sprayer



TY T	٩n	ш.	eп	FC	-	\mathbf{c}	TI	M	ĸ

PUMP	Silvan self-priming, oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised body. Direct coupled to 6.5HP Honda motor. BP125/20: 121L/min. capacity 2000 kPa.			
CONTROLS	3 outlet control with pressure regulator mounted on pump. Pressure gauge on control unit.			
TANK	1000/2000L polytuff impact resistant polyethylene construction. Calibrated sight line. Non-spill screw-down lid with breather.			
FRAME	Galvanised RHS steel construction with jockey wheel.			
AGITATION	Bypass action and venturi agitator.			

PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.					
FILTRATION	Suction line filter & lid strainer.					
WHEELS	Tubeless 29 x 13.5 - 15" turf tyres with galvanised rims on 1000L unit. Tubeless 31 x 13.5 - 15" turf tyres with galvanised rims on 2000L unit.					
HOSEREEL	30m of 19mm PVC hose and fish mouth fertiliser nozzle.		1			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)		
PR10-01	3400	1870	1825	275		
PR20-2	3500	1550	2100	400		

MODEL DESCRIPTION	CODE
1000L TURF SPRAYER: BP125/20 diaphragm pump, direct coupled to 6.5HP Honda motor, manual controls on pump and Pitarm hosereel with fish mouth nozzle.	PR10-01
2000L TURF SPRAYER: BP125/20 diaphragm pump, direct coupled to 6.5HP Honda motor, manual controls on pump and Pitarm hosereel with fish mouth nozzle.	PR20-2
FACTORY OPTIONS	CODE
6m Field boom	032-044-6
6m Devil boom with hydraulic fold	032-19D
8m Field boom	032-044-8
8m Devil boom with hydraulic fold	032-25D
10m Field boom	032-014-10
10m Devil boom with hydraulic fold	032-32DM
6, 8 and 10m Devil boom hydraulic lift	032-19DL
16L foam marker (double sided)	K99-39
Electric valve controls with pressure regulator and in cab pressure adjustment	K99-29
Bravo 180S automatic rate controller	J99-151
Note: Not all options will fit all models. Extra charges may apply to fitment of some options.	