Tray Mount Turf Sprayer



MODEL SPECIFICATIONS		
PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP60/20: 58 L/min capacity, 2000kPa pressure, direct driven by 5.5HP Honda with 6.1 reduction gear box.	
CONTROLS	3 section electric valves. Control box with pressure adjustment and on/off switches mounted on arm close to operator.	
TANK	400L Polytuff impact resistant polyethylene construction with calibratrated external sightline, non-spill screw-down lid, internal baffle and sump.	

FRAME	Fully galvanised RHS steel sled frame for fitment into tray body. Removable stand legs when not in use.
AGITATION	Bypass action and venturi jet.
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.
FILTRATION	Lid strainer and suction line strainer.
HOSEREEL	Economy hose reel with 20m x 12mm ag hose and Triam 49 spray gun.

MODEL DESCRIPTION		
400L TRAY DE-MOUNTABLE SLED SPRAYER: Sled mounted with BP60/20 pump with 5.5HP Honda engine, electric controls, economy reel, 20m hose and gun (no boom)		
FACTORY OPTIONS		
6m Field boom		
6m Devil boom with hydraulic fold		
16L Paddock foam marker (double sided)		
Bavo 180S automatic rate controller (includes BP125/20 pump upgrade)		
BP125/20 pump, 121 L/min capacity, 2000kPa driven by 5.5HP Honda		
Note: Not all ontions will fit all models. Extra charges may apply to fitment of some ontions.		