## Trailed Vineyard Herbicide



MODEL SPECIFICATIONS				
PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms & corrosion resistant, cast anodised aluminium body. BP125/20: 121L/min. capacity 2000 kPa pressure			
CONTROLS	Silvamatic 3 section electric valve on/off with in-cab electric pressure adjustment from control box.			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line & flip-top easy open lid.			
FRAME	Galvanised RHS steel construction, jockey wheel & adjustable tow hitch.			
AGITATION	Bypass action.			
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.			

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.

FILTRATION	Lid strainer & suction line strainer.					
WHEEL EQUIPMENT	SINGLE ROW: 50mm Duraflex axle with 50mm drop and sliding adjustment. 15" tyres on galvanised rims (max. speed rating 30 km/h).  3 ROW: Tandem suspension axle with 10" x 15" wheels.					
DTO DDIVECUALL						
PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.					
DIMENSIONS (WITH BOOM)	L (MM)	W (MM)	н (мм)	KG (DRY)		
JB2000-125	3000	1800	1530	400		
JB2000-1253RT	4600	1800	3300	990		

MODEL DESCRIPTION	CODE		
2000L TRAILED HERBICIDE SPRAYER: BP125/20 Pump, electric valve controls			
2000L TRAILED 3 ROW HERBICIDE SPRAYER: BP125/20 Pump (with under-vine and mid row booms)			
3000L TRAILED 3 ROW HERBICIDE SPRAYER: BP125/20 Pump (with under-vine and mid row booms)			
FACTORY OPTION			
Undervine and mid row boom (to suit JB2000-125)	032-HERB		
Bravo 180S automatic spray rate controller	J99-146		
Hydraulic drive centrifugal pump	J99-126		
Hydraulic row width and height adjustment			
When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be on order. Note: Extra charges may apply to fitment of some options.			