

Trailed Stiletto Powerhead 2000L



FOR MORE
INFORMATION ON
THE LEAF GUARD
SEE PAGE 22



Pictured: 2000L Stiletto Powerhead

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with brass heads and manifolds. IDS1701: 161L/min. capacity 5000kPa pressure.	FRAME	Galvanised steel with jockey wheel and adjustable drawbar.			
	FAN SIZE		920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.	AGITATION	Pump bypass plus venturi agitator.	
NOZZLES	24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl-plates per side.	PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
GEARBOX	Oil-bath type, 2-speed with neutral position.	FILTRATION	Lid strainer, suction line strainer and stainless steel nozzle filters.			
CONTROLS	40 bar electric section valves, master valve, electric pressure adjustment and in cab control.	WHEEL EQUIPMENT	Glideflex suspension axle with 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, easy open lid, 40mm drain valve, built-in 15L fresh water tank and chemical mixer.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity driveshaft with quick release pins & safety cover.			
		HP REQUIRED	Minimum 60 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		4100	1700	1500	680	
		DST23PF8G Length measured with drawbar in shortest position.				

MODEL DESCRIPTION	CODE
STILETTO 2000L: IDS1701 pump, 920mm Powerhead fan, electric valve controls, Glideflex axle, wide angle shaft	DST23PF8G
STILETTO 2000L: IDS1701 pump, 920mm Powerhead fan, Glideflex axle, wide angle shaft, Bravo 180S automatic rate controller	DST23PB8G
FACTORY OPTIONS	CODE
Leaf guard (to suit Powerhead)	D99-175
Twin nozzles (includes extra nozzles)	D99-182
Flotation tyres - 400/60 x 15.5" with fixed axle (in lieu of standard singles)	D99-80
Note: Not all options will fit all models. Extra charges may apply to fitment of some options.	