

Trailed Supaflo 3500L



Pictured: 3500L Supaflo with optional Powerhead conveyor

MODEL SPECIFICATIONS			
PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, anodised cast aluminium body with brass heads and manifolds. IDS1701: 161L/min. capacity, 5000kPa pressure. IDS2600: 249L/min. capacity, 5000kPa pressure.	FRAME	Galvanised steel with jockey wheel and adjustable drawbar.
FAN SIZE	900mm axial flow type, 10 bladed fan with curved nylon reinforced blades with air straightening vanes and protective mesh cover. Powerhead and Radak fitted with 920mm axial flow type, 10 bladed fan, centrifugal clutch and protective mesh cover.	AGITATION	Pump bypass plus venturi agitator.
NOZZLES	Flip-over type for dilute/concentrate spraying. Ceramic jets, stainless steel swirl-plates. 16 double sided nozzles (8 per side) twist on/off. The Powerhead has 24 double sided nozzles (12 per side) and the Radak has 32 (16 per side).	PRESSURE GAUGE	Glycerine filled gauge located on valve bank.
GEARBOX	2-speed with neutral position, oil-bath type.	FILTRATION	Lid strainer, suction line filter and nozzle cup strainers.
CONTROLS	40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.	WHEEL EQUIPMENT	Glideflex suspension axle fitted with 16" tyres and galvanised rims (speed rating 30km/h).
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, built-in chemical mixer and 40L fresh water hand wash tank.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity driveshaft with quick release pins & safety cover.
DIMENSIONS		L (MM)	W (MM)
DAB33AF7G		4755	1830
		1800	
		800	
Length measured with drawbar in shortest position.			

MODEL DESCRIPTION	CODE
SUPAFLO 3500L: IDS1701 pump, 900mm fan, electric valve controls, Glideflex axle	DAB33AF7G
SUPAFLO 3500L: IDS2600 pump, 900mm fan, electric valve controls, Glideflex axle	DAB36AF7G
FACTORY OPTIONS	
Powerhead Conveyor (in lieu of standard fan cowling)	D99-184
Radak Conveyor - Manual adjustment of top and bottom wings (in lieu of standard fan cowling)	D99-135
SCRAM Jet (to suit Radak conveyor)	D99-180
Hydraulic kit for Radak Conveyor (top wings)	D99-155B
Leaf guard (to suit Powerhead & Radak)	D99-175
Two-sided poly vineyard conveyor	D99-111
Twin nozzles (includes extra nozzles)	D99-182
Bravo 180S automatic rate controller	D99-143
BKT flotation tyres 558-400/55 - 22.5 (in lieu of standard singles)	D99-79
Tandem suspension axle with 10 x 15" wheels	D99-75
Note: Not all options will fit all models. Extra charges may apply to fitment of some options.	
Fitment of Powerhead & Radak includes upgrade to 920mm fan and uprated gearbox	