

Trailed G2 Supaflo 4000L



Orchards



Pictured: 4000L G2 Supaflo with Powerhead

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast aluminium body with brass heads and manifolds. IDS1701:161L/min. capacity, 5000kPa pressure.	HAND WASH TANK	60L polytuff tank filled through cap. Tap located next to chemical mixer hopper.			
FAN SIZE	920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.	MIXER TANK	Chemical mixer hopper with tap controls for rinse, transfer and main tank rinse. Venturi transfer back to main tank.			
NOZZLES	24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 Ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl plates per side. (16 per side with the Radak conveyor).	FRAME	Galvanised steel, heavy duty stand & adjustable drawbar.			
GEARBOX	2-speed with neutral position, oil-bath type.	AGITATION	Pump bypass plus venturi agitator.			
CONTROLS	40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.	PRESSURE GAUGE	Glycerine filled gauge located on valve bank.			
MAIN TANK	Polytuff impact resistant polyethylene construction with calibrated sight line. 50mm Camlock top & bottom fill.	FILTRATION	Suction line filter, pressure filter, nozzle cup strainers.			
FLUSH TANK	330L polytuff tank with top fill. Used to flush pump, filter, spray lines and nozzles.	WHEEL EQUIPMENT	Glideflex axle with 13.0/65 - 18" implement tyres (speed rating 30km/h).			
		PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity driveshaft with quick release pins & safety cover.			
		HP REQUIRED	Minimum 80 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		AB43PE2G	5550	1880	2020	1400
			Length measured with drawbar in shortest position.			

MODEL DESCRIPTION

SUPAFLO G2 4000L: IDS1701 pump, 920mm Powerhead fan, electric valve controls, Glideflex axle	AB43PE2G
SUPAFLO G2 4000L: IDS1701 pump, 920mm Radak fan, electric valve controls, Glideflex axle	AB43RE2G

FACTORY OPTIONS

FACTORY OPTIONS	CODE
Hydraulic kit for Radak Conveyor (top wings)	D99-155B
SCRAM Jet (to suit Radak conveyor)	D99-180
AVO Jet (to suit Radak conveyor)	D99-187
Leaf guard (to suit Powerhead & Radak)	D99-176
Twin nozzles (includes extra nozzles)	D99-182
Bravo 180S automatic rate controller	D99-143
Tandem suspension axle with 11.5/80 - 15.3 tyres	D99-78
BKT flotation tyres - 558-400/55 - 22.5 (in lieu of singles)	D99-79
IDS2001 pump,182L/min. capacity, 5000kPa pressure.	D99-148
IDS2600 pump,249L/min. capacity, 5000kPa pressure.	D99-149

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.