

Silvan Cannon Jet Sprayer



Flowers



Greenhouse



Vegetables



MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms, corrosion resistant, cast anodised aluminium body. APS96: 88L/min. capacity, 5000kPa pressure APS121: 115L/min capacity, 5000kPa pressure.	AGITATION	500L: Dual bypass 2000L: Pump bypass plus venturi agitator.			
FAN SIZE	450mm diameter twin turbine fan with galvanised frame and spray head. Hydraulic angle adjustment and manual top wing adjustment.	PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
NOZZLES	Flip-over type with ceramic hollow cone nozzles. 9 nozzles (6 in cannon head, 3 in side of cannon) with twist on/off.	FILTRATION	Lid strainer, suction line strainer and stainless steel nozzle filters.			
GEARBOX	Two speed with neutral position, oil-bath type.	2000L WHEEL EQUIPMENT	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
CONTROLS	40 bar electric section valves, master valve, electric pressure regulator and in cab controls.	PTO DRIVESHAFT	Quality driveshaft with quick release pins and safety cover.			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill lid. 40 litre fresh water tank fitted to 2000L unit.	HP REQUIRED	Minimum 75HP.			
FRAME	500L: Galvanised steel, suit cat I & II linkage 2000L: Galvanised steel with jockey wheel & adjustable drawbar.	DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		D05JET-96	1400	1190	2500	140
		D20JET-121GL	3750	1540	2500	640
		Length measured with drawbar in shortest position.				

MODEL DESCRIPTION

	CODE
CANNON JET 500L: APS96 pump, Cannon jet fan, electric valve controls	D05JET-96
CANNON JET 2000L: APS121 pump, Cannon jet fan, electric valve controls, Glideflex axle	D20JET-121GL

FACTORY OPTIONS

	CODE
Bravo 180S automatic rate controller	D99-143

Extra charges may apply to fitment of some options.